

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
30 August 2001 (30.08.2001)

PCT

(10) International Publication Number  
**WO 01/62681 A1**

(51) International Patent Classification<sup>7</sup>: C03C 17/38, 17/42, B05D 7/24

(21) International Application Number: PCT/US00/25359

(22) International Filing Date:  
13 September 2000 (13.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/512,861 24 February 2000 (24.02.2000) US

(71) Applicant: GLASS UNLIMITED OF HIGH POINT, INC. [US/US]; P.O. Box 528, High Point, NC 27261 (US).

(72) Inventor: EICHHORN, Keith, L.; 610 Emerywood Drive, High Point, NC 27262 (US).

(74) Agent: RHODES, C., Robert; Rhodes & Mason, P.L.L.C., P.O. Box 2974, Greensboro, NC 27402 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: GLASS PANEL WITH SIMULATED METAL STRIP



(57) Abstract: A glass panel having a simulated metal strip applied thereto in a decorative pattern, and a method for making a glass panel having a simulated metal strip applied thereto in a decorative pattern, including a flat panel of glass, a raised bead of air-curable acrylic resin applied in a prescribed pattern to at least one surface of the flat panel of glass, and a metal film overlying the bead of acrylic resin.

WO 01/62681 A1

## GLASS PANEL WITH SIMULATED METAL STRIP

### Background of the Invention

5 The present invention is directed to decorative glass panels, and, more particularly, to glass window and door panels having patterns that simulate strips of metal, such as chrome and brass.

In recent years, decorative glass has increased in popularity in both commercial and residential usage. It is now commonplace for decorative glass sheets to be used in buildings and homes in various types of doors such as entry, storm, and patio doors, as well as for exterior windows such as garden bath windows. Decorative glass has also become increasingly popular for interior glass doors, such as shower doors and French doors, as well as in furniture and architectural applications. As the scope and popularity of usage has grown, so has the demand for more affordable decorative glass products that simulate expensive materials and features.

10

15 Accordingly, cost effective methods for producing affordable high quality simulated decorative glass products are being sought.

The prior art discloses methods of forming patterns or lettering on materials other than paper, such as glass or plastic, by screen printing, stenciling, or painting. The most popular of these methods has been screen printing. However, its application has been limited to small items such as containers, bottles, dishes, cups, and glasses, and the inks have required UV, or radiation, curing. There is also known a method of applying a foil on top of screen-printed ink to achieve a metallic and attractive appearance, but it has been limited to smaller items and used exclusively for interior applications. These printed products do not stand up to exterior environmental conditions such as heat, cold, ultraviolet light, and moisture, and because they are screen printed, the final products lack a three-dimensional appearance.

20

25

### Summary of the Invention

The present invention is directed to a glass panel having decorative patterns formed on at least one surface, whereby those patterns simulate strips of metal, such as chrome and brass.

30

Accordingly, one aspect of the present invention is to provide a glass panel having a simulated metal strip applied thereto in a decorative pattern for interior applications such as French doors where exposure to the elements is not a concern. A flat panel of glass of the size and type appropriate for the application is chosen. Glass panels, including mirrors, may be annealed, strengthened, safety-tempered, laminated, or safety-backed. A raised bead of an air-curable acrylic resin is applied in a desired pattern to at least one surface of the glass panel. One such air-curable resin is formed by mixing a resin such as R.L. ACRY 14 or C.C.B. ACRY 14 with a resin hardener such as R.L.H. ACRY 15 or C.C.B.H. ACRY 15, manufactured by Creative Resins of Kent, England. To achieve the desired appearance, the raised bead of acrylic resin is optimally from about 2.0 mm to about 5.0 mm in width and from about 0.8 mm to about 1.1 mm in height. A metal film suitable for interior applications is heat-transferred from a film sheet to the cured resin bead. The film sheet is a substrate or backing sheet having a thin layer of aluminum deposited thereon. The metal film has an adhesive layer on the outer surface and a clear layer of protective material between the aluminum and the substrate. The outer layer of adhesive bonds the aluminum to the acrylic resin bead. To simulate different metals, a layer of dye can be included between the layer of aluminum and the clear layer of protective material. One metal film suitable for this interior application is manufactured by Crown Roll Leaf, Inc. in Patterson, New Jersey as item EXP-6884-E.

A second aspect of the present invention is to provide a decorative glass panel having a simulated metal strip for use in exterior environments or interior environments, such as baths and shower areas, where conditions are harsh. For such applications, the glass panel is annealed, tempered, or laminated and can be insulating or monolithic; i.e., a single uniform panel. The same acrylic resin used for the interior application is also suitable for exterior use. Following application and curing of the raised acrylic bead, a metal film suitable for exterior exposure is heat-transferred from a film sheet to the cured resin bead. The metal film must be capable of withstanding temperatures up to 200° F and must be impervious to moisture and ultraviolet light. One such metal film suitable for this application is manufactured by Foilmark-TPF in East Brunswick, New Jersey as item CR0-050-691 for chrome, and item CR-5055-

691 for brass-colored chrome. This film is also comprised of three layers. An outer layer of adhesive bonds to the raised acrylic bead. The second, or intermediate layer, is chrome, and the inner most layer is a clear protective material. Where a brass-colored appearance is desired, a layer of ferrous oxide is provided between the layer  
5 of chrome and the top layer of protective material.

A third aspect of the present invention is to provide a decorative window or door consisting of a peripheral support frame and a glass panel secured and supported by that frame. Depending upon the application chosen, the peripheral support frame desirably has a pair of opposed spaced-apart side walls and a pair of opposed spaced-apart end walls. The frame may be formed in any number of ways and using a variety  
10 of materials to support the glass panel including, for example, conventional wooden frames wherein the glass panel is placed within an opening formed in the frame and thereafter secured with peripheral molding or the like. The glass panel selected for the window or door would be formed as described in the first or second aspects above.

15

Another aspect of the present invention is to provide a method for making a glass panel having a simulated metal strip applied to at least one surface. A computer-driven plotter is used to apply a raised bead of air-curable acrylic resin in a desired pattern on a plotter table. One suitable computer-driven plotter is an X-Y  
20 plotter manufactured by International Robotix Industries, Inc. of Vancouver, British Columbia, Canada. Once the raised resin bead has been applied, the resin is allowed to air-cure for 24 to 48 hours at an ambient temperature of approximately 72 °F. Alternatively, higher ambient temperatures or convection heating will cure the resin at an accelerated rate. Before the metal film can be applied, the resin must be cured to a  
25 sufficient hardness. A durometer, an instrument consisting of a flat or blunt indenter point under pressure used to measure the hardness of materials, can be used for such a measurement. Specifically, when a durometer with a 1.0 mm flat point needle is completely compressed against the resin bead for 3 seconds, creating a force of 10  
Newtons at the needle, a reading of 65% or above on the 0 to 100% scale is ideal for  
30 the subsequent application of the metal film. This means that the resin bead will not deform during application of the metal film. The metal film described above, whether

for interior or exterior use, is applied in the same manner. Horizontal panels of glass are passed through a hot stamping machine, such as that manufactured by Acro Mark Company, Inc. of Berkeley Heights, New Jersey. A roll of metal film at least the width of the glass panel is brought into contact with the glass panel. A heated rubber roller presses the metal film against the raised acrylic resin bead causing it to bond to the bead. Because the adhesive layer in the metal film is specifically formulated for compatibility with the resin, and not the glass, the metal film corresponding only to the acrylic resin bead, and bonded thereto, is pulled off of the roll as the roll of metal film is lifted from the glass panel, after passing under the heated roller. Ideal bonding occurs at roller temperatures between about 300° F and 380° F for interior metal film and between about 350° F and 430° F for exterior metal film; however, these temperature ranges may vary as daily indoor ambient temperatures and glass panel surface temperatures vary. No post-curing or other treatment is required.

These and other aspects of the present invention will become apparent to those skilled in the art after a reading of the following description of the preferred embodiment when considered with the drawings.

#### **Brief Description of the Drawings**

Figure 1 is a front plan view of a decorative glass panel with a simulated metal strip attached thereto according to the present invention;

Figure 2 is a schematic, cross sectional view of the decorative glass panel taken along line 2-2 of Figure 1; and

Figure 3 is a front plan view of a decorative window or door according to the present invention.

#### **Description of the Preferred Embodiments**

Referring now to the drawings in general and Figure 1 in particular, it will be understood that the illustrations are for the purpose of describing a preferred embodiment of the invention and are not intended to limit the invention thereto. As

seen in Figure 1, a glass panel with a simulated metal strip attached thereto, generally designated 10, is shown constructed according to the present invention. The glass panel with simulated metal strip 10 includes a flat panel of glass 12 and simulated metal strip 14.

5 Referring to Figure 2, glass panel 12 has an outer surface 16 and an inner surface 18. A glass panel 12 of appropriate type and size is chosen for the particular application. Glass panels, including mirrors, may be annealed, strengthened, safety-tempered, laminated, or safety-backed. If intended for outside use, glass panel 12 can be insulating or monolithic; i.e., a single uniform panel.

10 The simulated metal strip 14 includes a raised bead of air-curable acrylic resin 20 and a metal film 21. The raised bead of acrylic resin 20 is applied to at least one of the surfaces 16, 18 of glass panel 12 to form a decorative pattern, the number of possible patterns being unlimited. To achieve the desired appearance, the raised bead of acrylic resin 20 is desirably from about 2.0 mm to about 5.0 mm in width and from  
15 about 0.8 mm to about 1.1 mm in height. One suitable air-curable acrylic resin is formed by mixing a resin such as R.L. ACRY 14 or C.C.B. ACRY 14, with a resin hardener such as R.L.H. ACRY 15 or C.C.B.H. ACRY 15, manufactured by Creative Resins of Kent, England. However, other comparable acrylic resins may be used.

20 To complete the simulated metal strip 14, a metal film 21 is heat-transferred from a film sheet to the cured bead of acrylic resin 20. The film sheet is a substrate or backing sheet having a layer of metal deposited thereon. Metal film 21 includes three layers 22, 24, and 28. An adhesive layer 22, specifically formulated to be compatible with both the resin and with metal, bonds the metal film 21 to the raised bead 20. An  
25 intermediate layer of metal 24 provides the metal appearance. For interior use, layer 24 is aluminum. Alternatively, for exterior use, layer 24 is chrome. Overlying layer 24 is a layer of protective material 28. To achieve a brass appearance, for interior use metal film 21 includes a layer of dye 26 between layer 24 and layer 28. Alternatively, for exterior use, layer 26 is ferrous oxide. One suitable metal film 21 for interior use  
30 is manufactured by Crown Roll Leaf, Inc. of Patterson, New Jersey as item EXP-6884-E. A suitable metal film 21 for exterior use is manufactured by Foilmark-TPF

of East Brunswick, New Jersey as item CRO-050-691 for chrome-colored film, and item CRO-5055-691 for brass-colored film.

Referring now to Figure 3, another aspect of the present invention is a decorative window or door, shown generally as 30, comprising a peripheral support frame 32 securing and supporting glass panel 40. The peripheral support frame 32 has a pair of opposed spaced apart side walls 36 and a pair of opposed spaced apart end walls 34, and may be formed in any number of ways and using a variety of materials to support glass panel 40 including, for example, conventional wooden frames wherein the glass panel is placed within an opening formed in the frame and thereafter secured with molding or the like. The glass panel 40 would be formed as shown in Figures 1 and 2 and described hereinabove.

Turning again to Figures 1 and 2, in making a glass panel having a simulated metal strip applied thereto, a raised bead of air-curable acrylic resin 20, as described above, is applied with a computer-driven plotter in a prescribed decorative pattern to a horizontal flat glass window or door panel 12 outer surface 16 or inner surface 18. One suitable computer-driven plotter is an X-Y plotter manufactured by International Robotix Industries, Inc. of Vancouver, British Columbia, Canada. The raised bead of acrylic resin 20 is then air-cured at an ambient temperature of approximately 72° F for 24 to 48 hours. Alternatively, exposure to convection heating or to higher ambient temperatures will accelerate the curing. The bead of acrylic resin 20 is cured to a sufficient hardness that will allow subsequent application of a metal film 21. A durometer, an instrument consisting of a flat or blunt indenter point under pressure used to measure the hardness of materials, can be used for such a measurement. Specifically, when a durometer with a 1.0 mm flat point needle is completely compressed against the resin bead 20 for 3 seconds, creating a force of 10 Newtons at the needle, a reading of 65% or above on the 0 to 100% scale is ideal for the subsequent application of the metal film 21. This means that the resin bead will not deform during application of the metal film. Metal film 21 is applied in the same manner, whether for interior or exterior applications. A horizontal glass panel 12 with a cured raised bead of acrylic resin 20 bonded thereto is passed through a hot stamping machine, such as that manufactured by Acro Mark Company, Inc. of

Berkeley Heights, New Jersey. A roll of metal film 21, at least as wide as the glass panel 12, is brought into contact with glass panel 12. A heated rubber roller presses the metal film 21 against the raised acrylic resin bead 20 as glass panel 12 passes under the roller. Because the adhesive layer in metal film 21 is specifically  
5 formulated for compatibility and bonding with the resin, and not the glass, metal film 21 corresponding only to the acrylic resin bead 20 pattern, and bonded thereto, is pulled off of the roll as the roll of metal film is lifted from glass panel 12 after passing under the heated rubber roller. Rubber roller temperatures of from about 300° F to about 380° F are ideal for the application of interior metal film and from about 350° F  
10 to 430° F for exterior metal film; however, these temperature ranges may vary as daily indoor ambient temperatures and glass panel surface temperatures vary. Upon removal from the hot stamping machine, the manufacture of a glass panel with a simulated metal strip 10 is complete. No post-curing or other treatment is required. If the user desires that the decorative pattern be applied on both outer surface 16 and  
15 inner surface 18 of glass panel 12, then the process described hereinabove is repeated.

Certain modifications and improvements will occur to those skilled in the art upon a reading of the foregoing description. It should be understood that all such modifications and improvements have been deleted herein for the sake of conciseness and readability but are properly within the scope of the following claims.

20



What is claimed is:

1. A glass panel having a simulated metal strip applied thereto in a decorative pattern, comprising:
  - (a) a flat panel of glass having an outer surface and an inner surface;
  - (b) a raised bead of air-curable acrylic resin applied in a prescribed pattern to at least one of said outer and inner surfaces of said glass panel; and
  - (c) a metal film overlying said bead of acrylic resin.
2. The glass panel of Claim 1 for use in interior environments wherein said raised bead of acrylic resin is about 2.0 mm to about 5.0 mm in width and about 0.8 mm to about 1.1mm in height.
3. The glass panel of Claim 1 for use in exterior environments wherein said metal film comprises:
  - a layer of adhesive for bonding to said raised bead of acrylic resin substrate;
  - an intermediate layer of aluminum; and
  - a layer of protective material.
4. The glass panel of Claim 3 further including a layer of dye between said layer of aluminum and said top layer of protective material.
5. The glass panel of Claim 1 for use in exterior or harsh environments wherein said flat panel of glass is tempered glass and said metal film comprises:
  - a bottom layer of adhesive for bonding to said raised bead of acrylic resin substrate;
  - an intermediate layer of chrome; and
  - a top layer of protective material.

6. The glass panel of Claim 5 further including a layer of ferrous oxide between said layer of chrome and said layer of protective material.

5 7. The glass panel of Claim 5 wherein said metal film is capable of withstanding temperatures up to 200° F and is impervious to moisture and ultraviolet light.

10 8. A decorative window or door, comprising:

(a) a peripheral support frame having a pair of opposed spaced apart side walls and a pair of opposed spaced apart end walls;

(b) a glass panel secured and supported by said frame, having:

15

(i) a flat panel of glass having an outer surface and an inner surface;

(ii) a raised bead of air-curable acrylic resin applied in a prescribed pattern to at least one of said outer and inner surfaces of said glass panel; and

20

(iii) a metal film overlying said bead of acrylic resin, wherein said metal film simulates a metal strip.

25 9. The glass panel of Claim 8 wherein said raised bead of acrylic resin is about 2.0 mm to about 5.0 mm in width and about 0.8 mm to about 1.1mm in height.

30

10. The glass panel of Claim 8 for use in interior environments wherein said metal film comprises:
- a layer of adhesive for bonding to said raised bead of acrylic resin;
  - an intermediate layer of aluminum; and
  - 5 a layer of protective material.
11. The glass panel of Claim 10 further including a layer of dye between said layer of aluminum and said layer of protective material.
12. The glass panel of Claim 8 for use in exterior or harsh environments wherein said flat panel of glass is tempered glass and said metal film comprises:
- a layer of adhesive for bonding to said raised bead of acrylic resin;
  - an intermediate layer of chrome; and
  - 15 a layer of protective material.
13. The glass panel of Claim 12 further including a layer of ferrous oxide between said layer of chrome and said layer of protective material.
14. The glass panel of Claim 12 wherein said metal film is capable of withstanding temperatures up to 200° F and is impervious to moisture and ultraviolet light.
15. A method for making a glass panel having a simulated metal strip applied thereto in a decorative pattern, comprising:
- (a) applying with an X-Y plotter a raised bead of air-curable acrylic resin in a prescribed pattern to a flat glass window or door panel surface;
  - (b) air curing said acrylic resin; and

(c) applying a metal film to said raised bead of acrylic resin at a temperature sufficient to bond said metal film to said raised bead of acrylic resin.

5           16.     The method of Claim 15 wherein said X-Y plotter applies said raised bead of acrylic resin to be between about 2.0 mm to about 5.0 mm in width and about 0.8 mm to about 1.1 mm in height.

10           17.     The method of Claim 15 wherein said acrylic resin bead is air-cured at about 72° F for about 24 to 48 hours until reaching a hardness of 65% on a 0% to 100% durometer scale when a 1.0 mm flat point needle is completely compressed against said resin bead for 3 seconds, creating a force of 10 Newtons at the needle.

15           18.     The method of Claim 15 wherein said metal film is applied by pressing said metal film for interior use against said raised bead of acrylic resin with a rubber roller heated to a temperature of about 300° F to 380° F.

20           19.     The method of Claim 15 wherein said metal film is applied by pressing said metal film for exterior use against said raised bead of acrylic resin with a rubber roller heated to a temperature of about 350° F to 430° F.

25




FIG. 1




FIG. 2




FIG. 3

## INTERNATIONAL SEARCH REPORT

Int'l Application No

PCT/US 00/25359

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C03C17/38 C03C17/42 B05D7/24

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C03C B05D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2 958 149 A (M. WENIG) 1 November 1960 (1960-11-01) claims 1-4	1,2
X	EP 0 626 354 A (REVLON CONSUMER PROD CORP) 30 November 1994 (1994-11-30) the whole document	1,2
X	DATABASE WPI Section Ch, Week 199817 Derwent Publications Ltd., London, GB; Class A23, AN 1998-188146 XP002156327 & JP 10 044353 A (DIAFOIL HOECHST CO LTD), 17 February 1998 (1998-02-17) abstract	1-19

-/--

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

\*&amp;\* document member of the same patent family

Date of the actual completion of the international search

27 December 2000

Date of mailing of the international search report

08/01/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Reedijk, A



## INTERNATIONAL SEARCH REPORT

Intern Application No

PCT/US 00/25359

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DATABASE WPI Section Ch, Week 197913 Derwent Publications Ltd., London, GB; Class A14, AN 1979-24443B XP002156328 & JP 54 022216 A (NISHIMURA H), 20 February 1979 (1979-02-20) abstract	1-5
A	US 3 547 766 A (CHU EDWARD) 15 December 1970 (1970-12-15) claims	1-19
A	DATABASE WPI Section Ch, Week 198238 Derwent Publications Ltd., London, GB; Class A97, AN 1982-79728E XP002156329 & JP 57 129842 A (KAMAYA CHEM IND CO LTD), 12 August 1982 (1982-08-12) abstract	1-19

## INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern

Application No

PCT/US 00/25359

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2958149	A	01-11-1960	NONE	
EP 0626354	A	30-11-1994	AU 661580 B	27-07-1995
			BR 9302378 A	17-01-1995
			CA 2096921 A,C	26-11-1994
			FI 932424 A	28-11-1994
			JP 7009796 A	13-01-1995
			NO 932066 A	08-12-1994
			NZ 247810 A	27-09-1994
			AT 156465 T	15-08-1997
			AU 3983293 A	01-12-1994
			DE 69312910 D	11-09-1997
			DE 69312910 T	20-11-1997
			DK 626354 T	22-09-1997
			ES 2105112 T	16-10-1997
			GR 3024646 T	31-12-1997
JP 10044353	A	17-02-1998	NONE	
JP 54022216	A	20-02-1979	NONE	
US 3547766	A	15-12-1970	NONE	
JP 57129842	A	12-08-1982	JP 1047415 B	13-10-1989
			JP 1685564 C	11-08-1992